

## Non-Slip Heat Shrink Tubing



**Model: NHST**

### Applications

Widely applied in tennis racket, badminton racket, fishing rod, baseball bat, billiard cue, hockey stick, industrial hand tool, athletic equipment and various handles. Increased friction and safety on smooth surfaces minimizes slipping.

### Characteristics

- ›Unique surface designed by environment friendly PE material for durable abrasion.
- ›Flannel decorative surface provides excellent sweat absorption.
- ›Ratio 50% (2:1) will be conveniently applied in covering irregular shape.
- ›Avoiding and solving girdle loosen up from handle
- ›Innovatory material designed for excellent performance and upgrade product value.
- ›Different colors and private pattern are available on request for individual design.
- ›Economical and easy to install, it's extremely proper to DIY market

### Technical Data

Test item	Value
Operation temperature	-55℃ to +110℃
Tensile strength	≥14Mpa
Shrinking temperature	Start at 60℃
Radial shrinking ratio	≥ 50%
Rated voltage	600V
Dielectric strength	≥25KV/mm
Volume resistance	10 <sup>14</sup> Ω.cm
Longitudinal shrinkage	<8%

**Specification**

SIZE	As supplied(mm)		After shrinkage(mm)		Standard Length/M
	I.D	W.T	I.D	W.T	
Φ10	≥Φ10	0.45±0.15	<Φ6.0	0.80±0.15	0.3
Φ15	≥Φ15	0.45±0.15	<Φ8.0	0.85±0.15	1.0
Φ20	≥Φ20	0.50±0.15	<Φ11.0	0.90±0.15	0.8/1.0/1.6
Φ22	≥Φ22	0.50±0.15	<Φ12.5	0.90±0.15	0.8/1.0/1.6
Φ25	≥Φ25	0.50±0.15	<Φ14.5	1.00±0.15	0.8/1.0/1.6
Φ28	≥Φ28	0.50±0.15	<Φ15.5	1.00±0.15	0.8/1.0/1.6
Φ30	≥Φ30	0.60±0.15	<Φ17.5	1.20±0.15	0.8/1.0/1.6
Φ35	≥Φ35	0.60±0.15	<Φ20.0	1.20±0.15	0.8/1.0/1.6
Φ40	≥Φ40	0.60±0.15	<Φ23.0	1.20±0.15	0.8/1.0/1.6
Φ45	≥Φ45	0.65±0.15	<Φ25.0	1.25±0.15	0.8/1.0/1.6
Φ50	≥Φ50	0.65±0.15	<Φ28.0	1.25±0.15	0.8/1.0/1.6